



# Encore's T.38 Fax Relay

## Platform

ADSP BF53x Series.

## Technology

The implementation, which is a real time fax relay, is in accordance with ITU-T T.38 recommendations

## Features

- Adheres to all the mandatory features of ITU-T T.38.
- Support up to and including 14,400 bps fax (V.17, V.29 and V.27ter)
- Multi-channel Capability.
- Relocatable Code & Data Modules.
- Interoperability tested against CISCO gateway and commercially available ATAs such as PLANET and PATTON.
- Inter operability tested using commercial fax machines and the Genoa Technology's FAXLAB™ T.30 test suite to ensure seamless T.30 relay.
- Supports redundancy for error protection in UDP mode of packet transfer. (Parity FEC, which is an optional scheme of error protection is not supported). The level of redundancy is configurable.
- Spoofing technique implemented so as to handle fixed latency and jitter in receiving IFP packets
- Tested for various IP network impairments such as latency, jitter, packet losses, out of order packet and duplicate packets. Maximum values of the impairments handled is as shown in the table below

Type of Impairment	Maximum Value
Fixed Latency (Round trip)	4 second
Jitter	1 second
Periodic Packet Loss (With level of redundancy > 1)	50%

- Provided in the form of Hardware Independent Library for easy porting to the target platform.

## Performance

<b>Code</b>	22 Kbytes
<b>Per Channel Data</b>	13 Kbytes
<b>Tables</b>	0
<b>MCPS</b>	4

\* Specifications are subject to change

## Availability

Now.

For further information please visit our web site, <http://www.ncoretech.com> or email to: [jp@ncoretech.com](mailto:jp@ncoretech.com) or contact:

**Encore Software Limited**  
6<sup>th</sup> Floor Leo Complex  
44 & 45 Residency Cross Road  
Bangalore 560 025, INDIA  
Tel: +91-80-4112 4291  
Fax: +91-80-2558 7690