



Encore's V.17 Fax Datapump

Processor

TMS320C55x Series.

Technology

The implementation supports ITU-T V.17, V.29, V.27ter and V.21 (High) Protocols. It enables fax operation at speeds ranging from 14.4 Kbps to 2.4 Kbps. The V.21 (High) Datapump supports the operation of T.30 Protocol.

Features

- Adheres to all the mandatory features of ITU-T V.17, V.29, V.27ter, V.21.
- 8 KHz Operation.
- HDLC Framing Support.
- Multi-channel Capability.
- Highly Optimised Assembly Implementation.
- Relocatable Code & Data Modules.
- Flexible Programming Interface ('C' Callable).
- Tested against various impairment combination using Standard Test Equipment.
- Provided in the form of Hardware Independent Library for easy porting to the target environment platform.
- Available as 'C' code, Optimised Assembly on TMS320C55x.

Performance

Code	23.15 K Bytes
Tables	2.4 K words
Per Channel Data	2.55 K words
Scratch Data	0.5 K words
MIPS	11.5

* Specifications are subject to change

Availability

The algorithm is immediately available both as object code and source code.

For further information please visit our web site, <http://www.ncoretech.com> or email to: ip@ncoretech.com or contact:

Encore Software Limited
6th Floor Leo Complex
44 & 45 Residency Cross Road
Bangalore 560 025, INDIA
Tel: +91-80-4112 4291 to 95
Fax: +91-80-2558 7690